



CL 390

Gewicht | Weight
205 kg (452 lbs)




CL 520

Gewicht | Weight
225 kg (496 lbs)

Herstellungsbedingte Abweichungen einzelner Maße innerhalb einer zumutbaren Toleranz sind nicht auszuschließen.
Auftragsbezogene Maße können gerne angefragt werden.

Production-related deviations in individual dimensions within an acceptable tolerance cannot be ruled out.
Requests for dimensions regarding a specific order are welcome.




Bauform 1 Anschlussstutzen mit Anschlussflansch und O-Ring in mm / inches
Design 1 Short, straight pipe connectors with connection flange and O-ring seal, in mm / inches

Baureihe / Size		CL 390							
		DIN				ANSI			
Nennweite [DN]	Dimension [in]	A		B		A		B	
		[mm]	[inches]	[mm]	[inches]	[mm]	[inches]	[mm]	[inches]
50	2"	153	6,02	601	23,66	172	6,77	639	25,16
80	3"	195	7,68	685	26,97	215	8,46	725	28,54
100	4"	160	6,30	615	24,21	184	7,24	663	26,10
125	5"	175	6,89	645	25,39	209	8,23	713	28,07
150	6"	160	6,30	615	24,21	194	7,64	683	26,89
200	8"	260	10,24	815	32,09	300	11,81	895	35,24
250	10"	295	11,61	885	34,84	329	12,95	953	37,52
300	12"	370	14,57	1.035	40,75	416	16,38	1.127	44,37

Baureihe / Size		CL 520							
		DIN				ANSI			
Nennweite [DN]	Dimension [in]	A		B		A		B	
		[mm]	[inches]	[mm]	[inches]	[mm]	[inches]	[mm]	[inches]
100	4"	260	10,24	815	32,09	284	11,18	863	33,98
125	5"	250	9,84	795	31,30	284	11,18	863	33,98
150	6"	165	6,50	625	24,61	199	7,83	693	27,28
200	8"	175	6,89	645	25,39	215	8,46	725	28,54
250	10"	245	9,65	785	30,91	279	10,98	853	33,58

Herstellungsbedingte Abweichungen einzelner Maße innerhalb einer zumutbaren Toleranz sind nicht auszuschließen.
Auftragsbezogene Maße können gerne angefragt werden.

Production-related deviations in individual dimensions within an acceptable tolerance cannot be ruled out.
Requests for dimensions regarding a specific order are welcome.




Bauform 2 90° Bogen oben in mm / inches
Design 2 90° elbow up in mm / inches

Baureihe / Size		CL 390							
		DIN				ANSI			
Nennweite [DN]	Dimension [in]	A		B		A		B	
		[mm]	[inches]	[mm]	[inches]	[mm]	[inches]	[mm]	[inches]
80	3"	259	10,20	813	32,01	259	10,20	813	32,01
100	4"	261	10,28	817	32,17	261	10,28	817	32,17
125	5"	310	12,20	915	36,02	310	12,20	915	36,02
150	6"	334	13,15	963	37,91	334	13,15	963	37,91
200	8"	503	19,80	1.301	51,22	503	19,80	1.301	51,22

Baureihe / Size		CL 520							
		DIN				ANSI			
Nennweite [DN]	Dimension [in]	A		B		A		B	
		[mm]	[inches]	[mm]	[inches]	[mm]	[inches]	[mm]	[inches]
100	4"	361	14,21	1.017	40,04	361	14,21	1.017	40,04
125	5"	385	15,16	1.065	41,93	385	15,16	1.065	41,93
150	6"	339	13,35	973	38,31	339	13,35	973	38,31
200	8"	418	16,46	1.131	44,53	418	16,46	1.131	44,53

Herstellungsbedingte Abweichungen einzelner Maße innerhalb einer zumutbaren Toleranz sind nicht auszuschließen.
Auftragsbezogene Maße können gerne angefragt werden.

Production-related deviations in individual dimensions within an acceptable tolerance cannot be ruled out.
Requests for dimensions regarding a specific order are welcome.




Bauform 6 Schwanenhals-Ausführung in mm / inches
Design 6 Gooseneck version in mm / inches

Baureihe / Size		CL 390							
		DIN				ANSI			
Nennweite [DN]	Dimension [in]	A		B		A		B	
		[mm]	[inches]	[mm]	[inches]	[mm]	[inches]	[mm]	[inches]
80	3"	423	16,65	1.141	44,92	443	17,44	1.181	46,50
100	4"	466	18,35	1.227	48,31	490	19,29	1.275	50,20
125	5"	555	21,85	1.405	55,31	589	23,19	1.473	57,99
150	6"	618	24,33	1.531	60,28	652	25,67	1.599	62,95
200	8"	870	34,25	2.035	80,12	910	35,83	2.115	83,27

Baureihe / Size		CL 520							
		DIN				ANSI			
Nennweite [DN]	Dimension [in]	A		B		A		B	
		[mm]	[inches]	[mm]	[inches]	[mm]	[inches]	[mm]	[inches]
100	4"	566	22,28	1.427	56,18	590	23,23	1.475	58,07
125	5"	630	24,80	1.555	61,22	665	26,18	1.625	63,98
150	6"	623	24,53	1.541	60,67	657	25,87	1.609	63,35
200	8"	785	30,91	1.865	73,43	825	32,48	1.945	76,57

Herstellungsbedingte Abweichungen einzelner Maße innerhalb einer zumutbaren Toleranz sind nicht auszuschließen.
Auftragsbezogene Maße können gerne angefragt werden.

Production-related deviations in individual dimensions within an acceptable tolerance cannot be ruled out.
Requests for dimensions regarding a specific order are welcome.



Standard-Aggregat-Ausführung in mm
Standard unit in mm / inches

Antrieb Drive		CL 390					
		Gewicht Weight		Abmessungen Dimensions			
				L1		H1	
[kw]	[hp]	[kg]	[lbs]	[mm]	[inches]	[mm]	[inches]
3,0	4,02	352	776,03	1.365	53,74	500	19,69
4,0	5,36	364	802,48	1.390	54,72	515	20,28
5,5	7,38	385	848,78	1.525	60,04	530	20,87
7,5	10,06	396	873,03	1.525	60,04	530	20,87
9,2	12,34	410	903,89	1.560	61,42	530	20,87
11,0	14,75	438	965,62	1.665	65,55	557	21,93
15,0	20,12	501	1.104,51	1.665	65,55	557	21,93
18,5	24,81	515	1.135,38	1.775	69,88	576	22,68

Antrieb Drive		CL 520					
		Gewicht Weight		Abmessungen Dimensions			
				L1		H1	
[kw]	[hp]	[kg]	[lbs]	[mm]	[inches]	[mm]	[inches]
3,0	4,02	376	828,94	1.406	55,35	500	19,69
4,0	5,36	388	855,39	1.431	56,34	415	16,34
5,5	7,38	409	901,69	1.566	61,65	530	20,87
7,5	10,06	420	925,94	1.566	61,65	530	20,87
9,2	12,34	435	959,01	1.601	63,03	530	20,87
11,0	14,75	462	1.018,53	1.706	67,17	557	21,93
15,0	20,12	526	1.159,63	1.706	67,17	557	21,93
18,5	24,81	540	1.190,49	1.816	71,50	576	22,68

Herstellungsbedingte Abweichungen einzelner Maße innerhalb einer zumutbaren Toleranz sind nicht auszuschließen.
Auftragsbezogene Maße können gerne angefragt werden.

Production-related deviations in individual dimensions within an acceptable tolerance cannot be ruled out.
Requests for dimensions regarding a specific order are welcome.