

Dimensions HPL 200 + 300



HPL 200

Weight: 110 kg
(243 lbs)




HPL 300

Weight: 130 kg
(287 lbs)

Börger GmbH | Benningsweg 24 | 46325 Borken-Weseke | GERMANY | Tel: +49 (2862) 9103-0 | www.boerger.com | 12/2012

Dimensions of different designs





Design 1 | Short, straight pipe connectors with connection flange and O-ring, in mm / inches (approx.)

		Size							
		HPL 200				HPL 300			
Nominal diameter:	Standard:	DIN/DIN EN		ANSI/ASME		DIN/DIN EN		ANSI/ASME	
	Dimension:	A	B	A	B	A	B	A	B
DN 100	mm	136	522	160	570	199	652	225	700
4"	inch	**5.35**	**20.55**	**6.30**	**22.44**	**7.83**	**25.67**	**8.86**	**27.56**
DN 125	mm	151	552	185	620	161	572	195	640
5"	inch	**5.95**	**21.73**	**7.28**	**24.41**	**6.34**	**22.54**	**7.68**	**25.20**
DN 150	mm	181	612	215	680	166	582	200	650
6"	inch	**7.13**	**24.10**	**8.46**	**26.77**	**6.54**	**22.91**	**7.87**	**25.61**
DN 200	mm	251	752	291	832	196	642	236	722
8"	inch	**9.88**	**29.61**	**11.46**	**32.76**	**7.72**	**25.28**	**9.29**	**28.43**

Production-related deviations in individual dimensions within an acceptable tolerance cannot be ruled out.
Requests for dimensions regarding a specific order are welcome.

Börger GmbH | Benningsweg 24 | 46325 Borken-Weseke | GERMANY | Tel: +49 (2862) 9103-0 | www.boerger.com | 12/2012





Standard-Aggregat-Ausführung in mm

Drive	Size					
	HPL 200			HPL 300		
	Weight	Dimensions		Weight	Dimensions	
		L1	H1		L1	H1
3 kW	194 kg	1,190 mm	414 mm	—	—	—
3 HP	**428 lbs**	**46.85 inch**	**16.30 inch**	—	—	—
4 kW	206 kg	1,216 mm	426 mm	220 kg	1,291 mm	426 mm
5 HP	**455 lbs**	**47.87 inch**	**16.77 inch**	**486 lbs**	**50.83 inch**	**16.77 inch**
5.5 kW	—	—	—	241 kg	1,328 mm	453mm
7.5 HP	—	—	—	**532 lbs**	**52.38 inch**	**17.83 inch**

Production-related deviations in individual dimensions within an acceptable tolerance cannot be ruled out.
Requests for dimensions regarding a specific order are welcome.