



Design 1 | Short, straight pipe connectors with connection flange and O-ring seal

Nominal diameter:	Size								
	Standard: Dimension:	EL 1000				EL 1550			
		DIN/DIN EN	ANSI/ASME	DIN/DIN EN	ANSI/ASME	DIN/DIN EN	ANSI/ASME	DIN/DIN EN	ANSI/ASME
DN 150 (6")	A	B	A	B	A	B	A	B	
DN 150 (6")	217	824	251	892	305	1.000	339	1.068	
DN 200 (8")	270	930	310	1.010	251	892	291	972	
DN 250 (10")	423	1.236	457	1.304	221	832	255	900	
DN 300 (12")	308	1.006	354	1.098	235	860	281	952	
DN 350 (14")	348	1.086	o. r.	o. r.	270	930	329	1.048	
DN 400 (16")	o. r.	o. r.	o. r.	o. r.	359	1.108	414	1.218	
DN 450 (18")	o. r.	o. r.	o. r.	o. r.	o. r.	o. r.	o. r.	o. r.	
DN 500 (20")	—	—	—	—	o. r.	o. r.	o. r.	o. r.	

Nominal diameter:	Size								
	Standard: Dimension:	EL 2250				EL 3050			
		DIN/DIN EN	ANSI/ASME	DIN/DIN EN	ANSI/ASME	DIN/DIN EN	ANSI/ASME	DIN/DIN EN	ANSI/ASME
DN 150 (6")	A	B	A	B	A	B	A	B	
DN 150 (6")	—	—	—	—	—	—	—	—	
DN 200 (8")	321	1.032	361	1.112	—	—	—	—	
DN 250 (10")	306	1002	340	1.070	o. r.	o. r.	o. r.	o. r.	
DN 300 (12")	296	982	342	1.074	o. r.	o. r.	521	1.432	
DN 350 (14")	325	1.040	384	1.158	491	1.372	o. r.	o. r.	
DN 400 (16")	385	1.160	440	1.270	400	1.190	455	1.300	
DN 450 (18")	o. r.	o. r.	o. r.	o. r.	458	1.306	o. r.	o. r.	
DN 500 (20")	o. r.	o. r.	o. r.	o. r.	498	1.386	568	1.526	

*o. r. = on request

Production-related deviations in individual dimensions within an acceptable tolerance cannot be ruled out. Requests for dimensions regarding a specific order are welcome.