



**Design 2 | 90° elbow up in mm (approx.)**

Nominal diameter:	Standard: Dimension:	Size							
		EL1000				EL 1550			
		DIN/DIN EN	ANSI/ASME	DIN/DIN EN	ANSI/ASME	DIN/DIN EN	ANSI/ASME	DIN/DIN EN	ANSI/ASME
DN 150 (6")		A	B	A	B	A	B	A	B
DN 200 (8")		391	1.172	o. r.	o. r.	494	1.378	494	1.378
DN 250 (10")		512	1.414	o. r.	o. r.	494	1.378	494	1.378
DN 300 (12")		737	1.864	o. r.	o. r.	534	1.458	534	1.458
DN 350 (14")		697	1.784	o. r.	o. r.	624	1.638	624	1.638
DN 350 (14")		o. r.	o. r.	o. r.	o. r.	735	1.860	735	1.860

Nominal diameter:	Standard: Dimension:	Size							
		EL 2250				EL 3050			
		DIN/DIN EN	ANSI/ASME	DIN/DIN EN	ANSI/ASME	DIN/DIN EN	ANSI/ASME	DIN/DIN EN	ANSI/ASME
DN 200 (8")		A	B	A	B	A	B	A	B
DN 250 (10")		—	—	—	—	—	—	—	—
DN 300 (12")		—	—	—	—	o. r.	o. r.	o. r.	o. r.
DN 350 (14")		o. r.	o. r.	o. r.	o. r.	o. r.	o. r.	o. r.	o. r.
DN 350 (14")		o. r.	o. r.	o. r.	o. r.	o. r.	o. r.	o. r.	o. r.

\*o. r. = on request

Production-related deviations in individual dimensions within an acceptable tolerance cannot be ruled out. Requests for dimensions regarding a specific order are welcome.