



Design 6 | Gooseneck version in mm / inches (approx.)

Nominal diameter:	Standard: Dimension:	Size							
		PL 100				PL 200			
		DIN/DIN EN	ANSI/ASME	DIN/DIN EN	ANSI/ASME	DIN/DIN EN	ANSI/ASME	DIN/DIN EN	ANSI/ASME
DN 40	mm	274	798	294	838	—	—	—	—
1½"	inch	10.79	31.42	11.57	32.99	—	—	—	—
DN 50	mm	328	906	347	944	308	866	327	904
2"	inch	12.91	35.67	13.66	37.17	12.13	34.09	12.87	35.59
DN 65	mm	332	914	357	964	366	982	391	1,032
2½"	inch	13.07	35.98	14.06	37.95	14.41	38.66	15.39	40.63
DN 80	mm	374	998	394	1,038	384	1,018	404	1,058
3"	inch	14.72	39.29	15.51	40.87	15.12	40.08	15.91	41.65
DN 100	mm	452	1,154	476	1,202	442	1,134	466	1,182
4"	inch	17.80	45.43	18.74	47.32	17.40	44.65	18.35	46.54
DN 125	mm	556	1,362	590	1,430	531	1,312	565	1380
5"	inch	21.89	53.62	23.23	56.30	20.91	51.65	22.24	54.33
DN 150	mm	634	1,518	668	1,586	639	1,528	673	1,596
6"	inch	24.96	59.76	26.30	62.44	25.16	60.16	26.50	62.83
DN 200	mm	846	1,942	886	2,022	861	1,972	901	2,052
8"	inch	33.31	76.46	34.88	79.61	33.90	77.64	35.47	80.79

Nominal diameter:	Standard: Dimension:	Size							
		PL 300				PL 400			
		DIN/DIN EN	ANSI/ASME	DIN/DIN EN	ANSI/ASME	DIN/DIN EN	ANSI/ASME	DIN/DIN EN	ANSI/ASME
DN 50	mm	—	—	—	—	—	—	—	—
2"	inch	—	—	—	—	—	—	—	—
DN 65	mm	—	—	—	—	—	—	—	—
2½"	inch	—	—	—	—	—	—	—	—
DN 80	mm	464	1,178	484	1,218	—	—	—	—
2½"	inch	18.27	46.38	19.06	47.95	—	—	—	—
DN 100	mm	507	1,264	531	1,312	572	1,304	551	1,352
4"	inch	19.96	49.76	20.91	51.65	22.52	51.34	21.69	53.23
DN 125	mm	541	1,332	575	1,400	568	1,368	602	1,454
5"	inch	21.30	52.44	22.64	55.12	22.36	53.86	23.70	57.24
DN 150	mm	624	1,498	658	1,566	649	1,548	683	1,616
6"	inch	24.57	58.98	25.91	61.65	25.55	60.94	26.89	63.62
DN 200	mm	806	1,862	846	1,942	831	1,912	871	1,992
8"	inch	31.73	73.31	33.31	76.46	32.72	75.28	34.29	78.43

Production-related deviations in individual dimensions within an acceptable tolerance cannot be ruled out. Requests for dimensions regarding a specific order are welcome.